

# COMMAND 110 Series

HME 110 ATC  
HME 110 C3

## Stay focused

When the pressure is on in control tower and C3 environments, choose a noise reducing headset with great call clarity to guarantee your performance. Closed ear cups provide excellent passive attenuation in particularly noisy spaces.

A noise-cancelling microphone ensures excellent speech transmission and can be adjusted to fit the requirements of your workplace. The soft ear pads and cushioned headband deliver long-wearing comfort so you can focus on what you do best. For dual communication switch from mono to stereo and enjoy integrated volume control on the head cup. The microphone can easily be repositioned to the left or right side via a flexible boom arm and includes a quick-fix feature for accurate placement. During tough shift work when every command counts, this is a headset that helps you make consistently reliable decisions.

See more at [eposaudio.com/command-hme110](https://eposaudio.com/command-hme110)



## Key benefits & features

### Clear communication with Voice Clarity

Voice enhancing technology with ultra noise-cancelling microphone for excellent voice transmission and reception on calls

### Stay focused with noise reduction

Closed ear cups offer passive attenuation up to 40 dB

### Control volume easily

With built in volume control on ear cup that can be disabled if necessary

### Choose your wearing style

With a flexible microphone boom arm worn on either the left or right

### Dual communication sources

Choose mono or stereo with simple switching between two communication sources

# COMMAND 110 Series

## Product data

Product	HME 110 ATC	HME 110 C3
Art. no.	500679	507280
EAN code	40 44155 00857 9	40 44155 23762 7
UPC code	6 15104 11322 0	6 15104 31485 6
<b>General</b>		
Cable length	1.5 m / 59.1 in	1.85 m / 72.8 in
Connector/cable termination	5.25mm jack plug microphone 6.35 mm jack plug headset	Open end, pre-tinned cable
Wearing style	Headband, double-sided	Headband, double-sided
Contact pressure	10 N	10 N
Ear coupling	Closed, Circumaural	Closed, Circumaural
Weight of headset	350 g / 12.35 oz	350 g / 12.35 oz
Storage temperature	-55 °C to +70 °C -67 °F to +158 °F	-55 °C to +70 °C -67 °F to +158 °F
Operating temperature	-10 °C to +55 °C +14 °F to +131 °F	-10 °C to +55 °C +14 °F to +131 °F
Warranty	5 years	5 years

<b>Headphones</b>		
<b>Sound pressure level:</b>		
dB SPL @ 1 KHz, 0.5 V	92 ±3 dB	92 ±3 dB
dB SPL @ 1 KHz, 1 mW	90 ±3 dB	90 ±3 dB
dB SPL @ 1 KHz, 1V	98 ±3 dB	98 ±3 dB
Max SPL [dB]	120	120
THD, total harmonic distortion at 95 dB SPL at 1 kHz	< 1 %	< 1 %
Frequency response	45 - 15,000 Hz	45 - 15,000 Hz
Impedance	300 Ω stereo / 150 Ω mono	300 Ω stereo / 150 Ω mono
Power rating	200 mW	200 mW
<b>Microphone</b>		
Microphone type	Electret, MKE 45-1	Electret, MKE 45-1
Output voltage	40 mV/Pa ±1dB @ 1kHz	40 mV/Pa ±1dB @ 1kHz
Pick-up pattern	Noise-cancelling, uni-directional	Noise-cancelling, uni-directional
Supply voltage	8-16 VDC	8-16 VDC
Frequency response	100 - 5,000 Hz	100 - 5,000 Hz
Recommended load impedance	150 - 2,200 Ω	150 - 2,200 Ω

# COMMAND 110 Series

## Product data

Packaging	HME 110 ATC	HME 110 C3
Dimension of product packaging (W x H x D)	230 x 170 x 105 mm 9.06 x 6.69 x 4.13 in	230 x 170 x 105 mm 9.06 x 6.69 x 4.13 in
Package weight (incl. complete product and packaging)	562 g / 19.82 oz	532 g / 18.77 oz
Units in distributor master carton	10	10
Master carton weight incl. products	6.48 kg / 14.29 lbs	6.18 kg / 13.62 lbs
Dimension of master carton (W x H x D)	590 x 290 x 350 mm 23.22 x 11.42 x 13.78 in	590 x 290 x 350 mm 23.22 x 11.42 x 13.78 in
Unit pack/end user	1	1
<b>Content of delivery</b>		
Box content	Headset, cable clip safety guide, quick guide	

