

COMMAND 600 Series

Unleash your potential with a headset that stands up to the daily demands of ATC/C3 working environments. EPOS Voice™ technology ensures excellent communication with an ultra noise-cancelling microphone – guaranteeing commands come through loud and clear.



Key Features

Excellent communication with EPOS Voice™ technology

Voice enhancing technology with ultra noise-cancelling microphone for excellent voice transmission and reception

Protect your hearing with EPOS ActiveGard®

Guards against acoustic injury without risk of communication drop-out

Extreme durability you can rely on

With stainless steel hinge on speaker joints which lasts for the long term

Exceptional comfort throughout your shift

With fully adjustable headband and generous leatherette ear pads made to maximize comfort

Choose your wearing style

With a flexible microphone boom arm worn on either the left or right

Product data

1/3

General

Contact pressure	SC 630: Approx. 1.0 N, SC 660: Approx. 1.5 N
Ear coupling	Supra-aural (On Ear)
Cable length	1.0 m / 3.28 ft. SC 665 C3: 1.8 m / 5.9 ft
Weight of headset	SC 630: 77 g/2.72 oz, SC 660: 110 g/3.88 oz
Storage temperature	-55 °C - +70 °C
Operating temperature	-15 °C - +55 °C
Connector	Mini-XLR. SC 665 is open-ended.
Warranty	2 years

Mircophone

Microphone type	Electret, ultra-noise cancelling
Sensitivity	-38 dBV/Pa (12.6 mV/Pa) @ 1 KHz, +/- 3 dB
Supply voltage	1-10 V DC
Frequency response	150 - 6,800 Hz

Product data

2/3

Product	SC 630 ATC/C3 AG	SC 660 ATC/C3 AG	SC 660 ATC/C3	SC 665 C3
Art. no.	1000296	1000297	1000298	1001014
EAN code	57 14708 00097 6	57 14708 00099 0	57 14708 00098 3	57 1470 800816 3
UPC code	8 40064 40097 8	8 40064 40099 2	8 40064 40098 5	8 40064 40816 5
Wearing style	SC 630: Headband with side-support.	SC 660: Headband	SC 660: Headband	SC 665: Headband
Headphones				
Sound pressure level:				
dB SPL @ 1 KHz, 0.5 V	103	103	103	101
dB SPL @ 1 KHz, 1 mW	88	88	86.5	93
dB SPL @ 1 KHz, 1V	95,5	95,5	99,5	107
Max SPL	103* dB	103* dB	120 dB	118 db
THD, total harmonic distortion	<1 % at 102 dB SPL at 1 kHz	<1 % at 102 dB SPL at 1 kHz	<1 % at 102 dB SPL at 1 kHz	<1 % at 102 dB SPL at 1 kHz
Frequency response	50 - 18,000 Hz	50 - 18,000 Hz	50 - 18,000 Hz	50 - 18,000 Hz
Impedance	200 Ω	200 Ω	200 Ω	40 Ω

Product data

3/3

Connector pin**:

Product	SC 260/SC 660 Series	SC 230/SC 630 Series	Headset cable wire colour
Pin 1	Mic GND	Mic GND	Shield
Pin 2	Mic +	Mic +	Red
Pin 3	SPK R***	Not connected in headset	Green
Pin 4	SPK L***	SPK +	Black
Pin 5	SPK GND	SPK GND	White

* Limited by EPOS ActiveGard®

** Seen from front of mini-XLR

*** L = mic boom arm side, R = opposite mic boom arm side

Product

COMMAND 600 Series

What's in the box

Headset, leatherette ear pads, mounted on headset, cable/clothing clip, mounted, nylon carry pouch

Spare parts

1/1

Product	Art. no.	Description	EAN code	UPC code
HZP 34	1000792	Leather Earpad SC 600 L, 2pcs	5714708005933	840064405935
HZP 36	1000793	Leather Earpad SC 600 L, 26pcs	5714708005940	840064405942
HZP 35	1000796	Leather Earpad SC 600 M, 2pcs	5714708005971	840064405973
HZP 37	1000797	Leather Earpad SC 600 M, 26pcs	5714708005988	840064405980
PS 01	1000783	Popshield 1 pc	5714708005841	840064405843
HPH 01	1000778	Hygiene cover (10 pcs)	5714708005797	840064405799
HPH 02	1000779	Hygiene cover (50 pcs)	5714708005803	840064405805